

Safety Data Sheet acc. to OSHA HCS

Print Date 11/22/2016

Revision Date 11/22/2016


- **Product Identifier**
 - **Trade Name:** EP11HT GRAY A
 - **Application of the Substance or Mixture:** Epoxy Resin
- **Details of the Supplier of the Safety Data Sheet (SDS)**
 - **Manufacturer or Supplier:**
Resinlab, LLC
N109 W13300 Ellsworth Drive,
Germantown, WI 53022
1-800-388-8605
www.resinlab.com
 - **Information Department:** Product Safety Department: msds@resinlab.com
 - **Emergency Telephone Number:**
North America - Chemtrec: 1-800-424-9300 (24 hours)
International - Chemtrec: 01-703-527-3887 (24 hours)

2 Hazard(s) identification

- **Hazard Classification**
 - Skin Irrit. 2 H315 Causes skin irritation.
 - Eye Dam. 2B H320 Causes eye irritation.
 - Skin Sens. 1 H317 May cause an allergic skin reaction.
 - Muta. 2 H341 Suspected of causing genetic defects.
 - Carc. 2 H351 Suspected of causing cancer.

- **Label Elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).



- **Signal Word** Warning

- **Hazard-determining Component(s)**

Bisphenol-A-(epichlorohydrin) epoxy resin
Butylglycidylether

- **Hazard statements**

H315+H320 Causes skin and eye irritation.
H317 May cause an allergic skin reaction.
H341 Suspected of causing genetic defects.
H351 Suspected of causing cancer.

- **Precautionary statements**

Avoid breathing dust/fume/gas/mist/vapors/spray
Wear protective gloves/protective clothing/eye protection/face protection.
Wash thoroughly after handling.
Contaminated work clothing must not be allowed out of the workplace.
Do not handle until all safety precautions have been read and understood.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Wash contaminated clothing before reuse.
If exposed or concerned: Get medical advice/attention.
If skin irritation occurs: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.
IF ON SKIN: Wash with plenty of water.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Hazard Rating System**

- **NFPA System**

- **NFPA Ratings (scale 0 - 4)**



NFPA special hazards (water reactivity and oxidizing property): None

- **HMIS System**

- **HMIS Ratings (scale 0 - 4)**



- **Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

Safety Data Sheet acc. to OSHA HCS

Print Date 11/22/2016

Revision Date 11/22/2016

Trade Name: EP11HT GRAY A

(Contd. of page 1)

3 Composition/information on ingredients

Chemical Characterization: Mixtures

Composition/Information on Ingredients

CAS: 25068-38-6 NLP: 500-033-5 Index Number: 603-074-00-8	Bisphenol-A-(epichlorohydrin) epoxy resin Aquatic Chronic 2, H411 Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317	70-80%
CAS: 1317-65-3 EINECS: 215-279-6 RTECS: EV 9580000	Calcium Carbonate	10-20%
CAS: 67762-90-7 EC number: 614-122-2	Siloxanes and Silicones, di-Me, reaction products with silica	2.5-5%
CAS: 2426-08-6 EINECS: 219-376-4 Index Number: 603-039-00-7 RTECS: TX 4200000	Butylglycidylether Flam. Liq. 3, H226 Muta. 2, H341; Carc. 2, H351 Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Sens. 1, H317 Aquatic Chronic 3, H412	2.5-5%

Classification System:

The Classifications were based on the Toxicological and Ecological Data of the substances/mixtures in the Section 11 and 12.

Additional Information:

If the chemical name/CAS number is proprietary and or weight percentage is listed as a range, the specific chemical identity and or percentage of composition has been withheld as a trade secret.

4 First-aid measures

Description of First Aid Measures

General Information

Ensure medical personnel are aware of exposure and take precautions for their personal protection; see Section 8 for the information of personal protection.

After Inhalation

Remove victim from exposure to fresh air. Keep person at rest. Provide oxygen if person is not breathing.
In case of unconsciousness place patient stably in side position for transportation.
Supply fresh air; consult doctor in case of complaints.

After Skin Contact

Remove all contaminated clothing and wash before reuse.
Wash contaminated skin with water and soap and rinse thoroughly.
Seek medical treatment in case of complaints.

After Eye Contact

Immediately bathe eyes for 15 minutes under running water.
Immediately remove contact lenses if present. Continue rinsing.
Seek medical treatment in case of complaints.

After Swallowing

If victim is unconscious; never give anything by mouth.
If victim is conscious; rinse out mouth and give victim small amounts of water.
Seek medical treatment in case of complaints.

After Exposure Seek medical treatment in case of complaints.

Information for Doctor Have chemical containers, labels and/or (M)SDS ready when calling or visiting a medical center.

Indication of any Immediate Medical Attention and Special Treatment Needed

After frequent or high intense exposure, the following medical tests are recommended:
eye tests
skin tests
Check section 11 Toxicological Information for further relevant information.

Additional Information

For additional information, please consult the corresponding first aid measures in the most current version of Emergency Response Guidebook which is produced by the US Department of Transportation.

5 Fire-fighting measures

Extinguishing Media

Suitable Extinguishing Agent(s)

Use fire fighting measures and extinguishing agents that suit the environment.
In case of fire, suitable extinguishing agents are:
Alcohol resistant foam.
Dry chemical or fire-extinguishing powder.
Carbon dioxide (CO₂).
Water spray or water fog.

Unsuitable Extinguishing Agent(s) Water with full jet

Firefighting Procedures

Isolate fire and deny unnecessary entry.
Immediately withdraw all personnel from the area in case of rising sound from venting safety device.
Eliminate all ignition sources if safe to do so.
Do not extinguish fire unless flow can be stopped.
Burning liquids may be moved by flushing with water; protect personnel and minimize property damage.
Fight fire from protected location or safe distance.
Contain fire water runoff if possible to prevent environmental pollution.

Special Hazards Arising in Fire

Will not burn unless preheated.

(Contd. on page 3)

Safety Data Sheet acc. to OSHA HCS

Print Date 11/22/2016

Revision Date 11/22/2016

Trade Name: EP11HT GRAY A

(Contd. of page 2)

In case of fire, following can be released:

Phenolic compounds

Formaldehyde, a skin and lung sensitizer and a regulated carcinogen, may be formed during fires.

 Carbon dioxide (CO₂) and Carbon monoxide (CO)

Calcium oxide (CaO)

 Silicon oxide (SiO₂)

Advice for Firefighters

If employees are expected to fight fires, they must be trained and equipped as stated in the OSHA fire brigades standard (29 CFR 1910.156).

As with any fire, wear positive-pressure self-contained breathing apparatus and full protective gear that are NIOSH approved.

Additional Information Ensure adequate and functional fire fighting facilities equipped in working area at all times.

6 Accidental release measures

Personal Precautions

Do not breathe gas, vapors, dusts or mists if their inhalable particles occur during use.

Ensure personnel take precautions for their personal protection during clean up; see Section 8 for the specific requirements.

Environmental Precautions No further relevant information.

Cleaning Up Methods

Ensure adequate ventilation.

Eliminate all ignition sources.

Keep unauthorized personnel away.

For large spills:

Shut off source of leak if safe to do so.

Dike and contain.

Remove with vacuum trucks or pump to storage/salvage vessels.

Allow molten product to cool.

Absorb residues with liquid-binding materials.

For small spills:

Ventilate and wash area after clean-up is complete.

Collect spills in suitable and properly labeled containers.

Do not use solvents unless following safe handling practices and within the recommended exposure guidelines.

Dispose contaminated chemicals as waste according to Section 13.

Additional Information No further relevant information.

Protective Action Criteria for Chemicals

PAC-1:

25068-38-6	Bisphenol-A-(epichlorohydrin) epoxy resin	90 mg/m ³
67762-90-7	Siloxanes and Silicones, di-Me, reaction products with silica	120 mg/m ³
2426-08-6	Butylglycidylether	9 ppm
1333-86-4	Carbon black	9 mg/m ³

PAC-2:

25068-38-6	Bisphenol-A-(epichlorohydrin) epoxy resin	990 mg/m ³
67762-90-7	Siloxanes and Silicones, di-Me, reaction products with silica	1,300 mg/m ³
2426-08-6	Butylglycidylether	580 ppm
1333-86-4	Carbon black	99 mg/m ³

PAC-3:

25068-38-6	Bisphenol-A-(epichlorohydrin) epoxy resin	5,900 mg/m ³
67762-90-7	Siloxanes and Silicones, di-Me, reaction products with silica	7,900 mg/m ³
2426-08-6	Butylglycidylether	3,500 ppm
1333-86-4	Carbon black	590 mg/m ³

7 Handling and storage

Handling

Precautions for Safe Handling

Keep away from incompatible material(s).

Avoid any release into the environment.

For industrial or professional use only

Observe all the personal protection requirements in Section 8.

Information about Protection Against Explosions and Fires

Will not burn unless preheated.

Keep away from heat, sparks, open flame and other ignition sources during handling.

Storage

Requirements to be Met by Storerooms and Receptacles

Store in a well-ventilated place; provide ventilation for receptacles.

Keep stored in accordance with local, regional, national, and international regulations.

Information about Storage in One Common Storage Facility

Store away from incompatible material(s).

Store away from foodstuffs.

Avoid release to the environment.

Additional Information No further relevant information.

(Contd. on page 4)

Safety Data Sheet acc. to OSHA HCS

Print Date 11/22/2016

Revision Date 11/22/2016

Trade Name: EP11HT GRAY A

(Contd. of page 3)

8 Exposure controls/personal protection

Engineering Measures or Controls

Exposure Limit Values that Require Monitoring at the Workplace

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the remaining constituent has no known exposure limits.

1317-65-3 Calcium Carbonate

TEEL	Short-term value: 15.0 mg/m ³ Long-term value: 60.0 mg/m ³ SCAPA, 2008
------	--

67762-90-7 Siloxanes and Silicones, di-Me, reaction products with silica

OSHA PEL	Short-term value: 15 mg/m ³
US ACGIH	Short-term value: 10 mg/m ³

2426-08-6 Butylglycidylether

PEL	Long-term value: 270 mg/m ³ , 50 ppm
REL	Ceiling limit value: 30 mg/m ³ , 5.6 ppm *15-min
TLV	Long-term value: 16 mg/m ³ , 3 ppm Skin; DSEN

1333-86-4 Carbon black

PEL	Long-term value: 3.5 mg/m ³
REL	Long-term value: 3.5* mg/m ³ *0.1 in presence of PAHs; See Pocket Guide Apps.A+C
TLV	Long-term value: 3* mg/m ³ *inhalable fraction

Other Engineering Measures or Controls

Ventilation rates should be matched to conditions.

If applicable, use process enclosure(s), local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits.

Personal Protective

General Protective and Hygienic Measures

Avoid any contact with eye.

Do not eat, drink or smoke during work.

Clean hands and exposed skin thoroughly after work and before breaks.

Personal Protective Equipment (PPE)

Breathing Equipment

Sufficient ventilation in pattern and volume should be provided in order to maintain air contaminant levels below recommended exposure limits.

Use a NIOSH approved air-purifying organic vapor respirator if occupational limits are exceeded. For emergency situations, confined space use, or other conditions where exposure limits may be greatly exceeded, use an approved air supplied respirator. Observe OSHA regulations (29CFR 1910.134) for respirator use.

Hand Protection

Selection of glove material should take into consideration the penetration times, rates of diffusion, and the degradation.

Suggested glove type(s):



Protective gloves

Nitrile Gloves
Butyl Rubber Gloves

Eye Protection



Safety glasses

safety glasses with side shields and or face shield.

Body Protection Appropriate chemical resistant clothing.

Additional Information

All protective clothing (suits, gloves, footwear, headgear) should be clean, available every day, and put on before work.

The Engineering measures or controls, and PPE recommendations are only guidelines and may not apply to every situation. For additional information, please consult the corresponding requirements under OSHA 29 CFR 1910.94-95, and 29 CFR 1910.132-138.

9 Physical and chemical properties

Information on Basic Physical and Chemical Properties

Appearance:

Form:

Color:

Odor:

Odor Threshold:

Paste

Dark gray

Mild epoxy odor

Not determined.

PH-Value:

Not determined.

(Contd. on page 5)

Safety Data Sheet acc. to OSHA HCS

Print Date 11/22/2016

Revision Date 11/22/2016

Trade Name: EP11HT GRAY A

(Contd. of page 4)

· Change in Condition:	
· Melting Point:	Not determined.
· Boiling Point:	Not determined.
· Flash Point:	<249 °C (<480 °F) (Estimated)
· Decomposition Temperature:	Not determined.
· Auto-ignition Temperature:	Not determined.
· Flammability:	Not determined.
· Explosion:	Not determined.
· Explosion Limits:	
· Lower:	Not determined.
· Upper:	Not determined.
· Vapor Pressure:	Not determined.
· Vapor Density:	not determined
· Density at 20 °C (68 °F):	1.26 g/cm ³ (10.515 lbs/gal) (ASTM R050-16)
· Solubility in or Miscibility with Water:	Not miscible or difficult to mix.
· VOC Content(s):	3.3%
· Segregation coefficient LogPow (n-octanol/water):	Not determined.
· Henry's Law Constant:	Not determined.
· Viscosity:	
· Dynamic at 20 °C (68 °F):	800000 mPas (ASTM R050-12)
· Kinematic:	Not determined.
· Additional Information	No further relevant information.

10 Stability and reactivity

- **Physical Hazard(s)** Not a regulated reactive or physical hazard under GHS.
- **Hazardous Reactivity and Chemical Stability** May polymerize when heated.
- **Thermal Decomposition and Conditions to be Avoided**
Keep away from incompatible material(s).
Thermally decomposes during fire or high heat; keep away from heat, sparks, open flame and other ignition sources.
- **Possibility of Other Hazardous Reaction(s)** No further relevant information available.
- **Incompatible Material(s)**
Oxidizing agents
Mercaptans
Acids
Amines.
Bases (Alkalis)
- **Hazardous Decomposition Product(s)**
Irritating fumes
Thermally decomposes during fire or very high heat. See Section 5 for fire hazards evolved during thermal decomposition.
- **Hazardous Polymerization Product(s)** Will not occur.
- **Additional Information** No further relevant information.

11 Toxicological information

· Acute Toxicity

· Oral

25068-38-6 Bisphenol-A-(epichlorohydrin) epoxy resin

Oral	LD50	11400 mg/kg (rat) 15600 mg/kg (mouse) Reference: NLM Toxnet (2010).
------	------	---

1317-65-3 Calcium Carbonate

Oral	LD50	6450 mg/kg (rat) Reference: Imerys (M)SDS (2008).
------	------	--

67762-90-7 Siloxanes and Silicones, di-Me, reaction products with silica

Oral	LD50	>5000 mg/kg (rat) (test method not specified) Reference: Cabot (M)SDS (2012).
------	------	--

2426-08-6 Butylglycidylether

Oral	LD50	1530 mg/kg (mouse) 1660 mg/kg (rat) Reference: NLM Toxnet (2011).
------	------	---

· Potential Health Effect(s):

While not a classified acute oral hazard, the product may cause the following symptom(s):
See acute inhalative effect(s) for further information

· Dermal

25068-38-6 Bisphenol-A-(epichlorohydrin) epoxy resin

Dermal	LD50	20000 mg/kg (rabbit) (Test guideline not available) > 1270 mg/kg (mouse) > 2000 mg/kg (rat) > 1600 mg/kg (rabbit); however, there was no fixed test result available; classification was not possible without further information.
--------	------	---

(Contd. on page 6)

Safety Data Sheet acc. to OSHA HCS

Print Date 11/22/2016

Revision Date 11/22/2016

Trade Name: EP11HT GRAY A

(Contd. of page 5)

1317-65-3 Calcium Carbonate

Dermal LD50 No data available.

67762-90-7 Siloxanes and Silicones, di-Me, reaction products with silica

 Dermal LD50 (Test species: n/a) (Toxicity not expected based on acute oral data)
 Based on the acute oral toxicity test, it was expected that toxicity to mammals via dermal application of the substance was not a significant concern and resulted in a similar lack of acute toxicity. Thus, the substance was not classified as an acute dermal hazard as a wetted form.

2426-08-6 Butylglycidylether

 Dermal LD50 2290 mg/kg (rabbit) (Estimated from LD50 of 2.52mL/kg)
 > 2150mg/kg (rabbit)
 Reference: ChemID (2011).

Potential Health Effect(s):

 No further relevant information available; classification is not possible.
 See acute inhalative effect(s) for further information.

Inhalative
25068-38-6 Bisphenol-A-(epichlorohydrin) epoxy resin

Inhalative LC50/4 h (Test species: n/a) (Toxicity not expected based on the acute oral data)

1317-65-3 Calcium Carbonate

Inhalative LC50/4 h No data available.

67762-90-7 Siloxanes and Silicones, di-Me, reaction products with silica

 Inhalative LC50/4 h (Test species: n/a) (Toxicity not expected based on acute oral data)
 Due to wetted form of the substance, inhalative effects from dust form can be seen as negligible. Meanwhile, based on the acute oral toxicity test, it was expected that toxicity to mammals via inhalation of the substance was not a significant concern and resulted in a similar lack of acute toxicity. Thus, the substance was not classified as an acute inhalation hazard.

2426-08-6 Butylglycidylether

 Inhalative LC50/4 h 10.96 mg/l (rat) (LC50/4 hrs; calculated from LC50/8 hrs of 1030 ppm)
 Reference: ChemID and EnviChem (2011).

Potential Health Effect(s):

 In inhaled, may cause:
 While not possible to classify the acute inhalative hazard due to missing data, the product may cause the following symptom(s):
 wheezing
 incoordination
 fainting
 cough, headache, sore throat, and passing out

Skin Corrosion or Irritation
25068-38-6 Bisphenol-A-(epichlorohydrin) epoxy resin

 Corrosion/Irritation irritating (rabbit)
 Acute skin irritation was mild, through repeated and prolonged exposure may cause severe irritation.
 The substance was classified as Category 2 by GHS-J.
 Reference: HSNO CCID (2010) and GHS-J (2006).

1317-65-3 Calcium Carbonate

 Corrosion/Irritation moderately
 The substance is moderately irritating based on the PH = 9.5 with concentration of 50g/L of water at 20C.

 moderately (rabbit) (Draize test)
 500 mg/24h, the pure substance shows no irritating effect, however, the impurities or degradation products may lead to irritant effects on the sweating skin due to alkalinity.
 Reference: IUCLID dataset of CAS No. 471-34-1 (2000).

67762-90-7 Siloxanes and Silicones, di-Me, reaction products with silica

 Corrosion/Irritation Non-irritating (Test species: n/a) (Primary irritation index=0)
 mildly irritating (rabbit) (Read across from CAS 63148-62-9)
 No test detail available; for safety reasons, the substance was classified as mildly irritating (Category 3) to rabbit skin.
 Reference: HSNO CCID (2010).

2426-08-6 Butylglycidylether

 Corrosion/Irritation irritating (rabbit) (Draize test)
 Draize score was 3.3; thus, the substance was classified as a Category 2 skin irritant.
 irritating (human)
 Reference: HSNO CCID (2011).

Potential Health Effect(s):

 Causes skin irritation.
 In contact with skin, may cause:
 redness and pain

Eye Serious Damage or Irritation
25068-38-6 Bisphenol-A-(epichlorohydrin) epoxy resin

 Damage/Irritation irritating (rabbit)
 The substance caused eye irritation (Category 2A) based on the dermal effect to rabbit skin.

1317-65-3 Calcium Carbonate

 Damage/Irritation slightly (Human)
 The substance is slightly irritating to the eyes.
 Reference: IUCLID Dataset of CAS No. 471-34-1 (2000).

(Contd. on page 7)

Safety Data Sheet acc. to OSHA HCS

Print Date 11/22/2016

Revision Date 11/22/2016

Trade Name: EP11HT GRAY A

(Contd. of page 6)

	not irritating (rabbit) No toxic effect when applied to surface of rabbit eyes Reference: ACToR of CAS No. 471-34-1 (2010).
--	---

67762-90-7 Siloxanes and Silicones, di-Me, reaction products with silica

Damage/Irritation	slightly irrit. (Human) (Read across from CAS 63148-62-9) non-irritating (Primary irritation index=0) Transient ocular irritation was observed in humans, rabbits, dogs, and monkeys after injection of the substance to their eye bodies. However, those effects can be seen as negligible based on regular use of the substance. When applying lower viscosity substance-oil mixture to human and rabbit eyes, there was no cornea injury, but a delay of healing of the existed corneal erosion observed. For safety reasons, the substance was classified as a slight eye irritant (Category 2B). Reference: ACToR (2011) and Cabot (M)SDS (2012).
-------------------	---

2426-08-6 Butylglycidylether

Damage/Irritation	mildly irrit. (rabbit) The substance caused reversible damage to rabbit eyes when applied as drops. Reference: HSDB (2011).
-------------------	---

- **Potential Health Effect(s):**
Causes serious eye irritation.
Causes eye irritation.
In contact with eye, may cause:
redness and pain
unlikely to cause corneal injuries

• Respiratory or Skin Sensitization

25068-38-6 Bisphenol-A-(epichlorohydrin) epoxy resin

Sensitization	Skin	sensitizing (Human) Based on positive results from skin sensitization tests on human volunteers and guinea pigs, GHS-J classified the substance as a dermal sensitizer. Reference: GHS-J (2006).
	Respiratory	(No data available)

1317-65-3 Calcium Carbonate

Sensitization	Skin	No data available.
	Respiratory	No data available.

67762-90-7 Siloxanes and Silicones, di-Me, reaction products with silica

Sensitization	Skin	(No data available) Primary irritation Index=0 Non-irritating. Cabot MSDS (2012)
	Respiratory	(No data available)

2426-08-6 Butylglycidylether

Sensitization	Skin	sensitizing (Human) (Patch test) 5 out of 5 human subjects treated with neat substance showed positive reactions; 17 out of 25 human subjects treated with 10% concentrated solution of the substance showed positive reactions. Thus, the substance was classified as a skin sensitizer to humans. Reference: HSDB (2011).
	Respiratory	(No data available)

- **Potential Health Effect(s):**
May cause an allergic skin reaction.
Repeated skin contact may cause dermatitis, skin rash or itchiness.
No relevant information for respiratory sensitization; classification is not possible.

• OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

• Germ Cell Mutagenicity

25068-38-6 Bisphenol-A-(epichlorohydrin) epoxy resin

Mutagenicity	positive (Chinese hamster lung fibroblast cells) (In Vitro (Chromosomal Aberration)) In Vitro (Chromosomal Aberration; Chinese hamster lung fibroblast cells) - Positive without metabolic activation; negative with metabolic activation. Positive (salmonella typhimurium) (In Vitro (Ames assay)). Due to the absence from In Vivo tests, it was not possible to make a conclusion of mutagenicity of the substance. Reference: NLM CCRIS (2010).
--------------	---

1317-65-3 Calcium Carbonate

Mutagenicity	negative The pure substance is not listed as a carcinogen by NTP, IARC or OSHA. Reference: Imerys (M)SDS (2008).
--------------	--

67762-90-7 Siloxanes and Silicones, di-Me, reaction products with silica

Mutagenicity	negative (Chinese Hamster) (In Vitro (AMES Test)) negative (Chinese Hamster) (In Vitro (Chromosomal aberration in ovary cells)) Reference: Cabot (M)SDS (2012).
--------------	---

2426-08-6 Butylglycidylether

Mutagenicity	positive (salmonella typhimurium) (In Vitro (Ames test)) Studies on Butyl Glycidyl Ether showed it to be mutagenic and genotoxic in bacterial and mammalian cell systems. (Germ cell mutagen Group 2) positive (Human) (In Vivo (DNA repair with mononucleated leukocytes)) negative (mouse) (In Vivo (Dominant lethal&Micronucleus assay)) REACH CLP, NIOSH ICSC, NJ-RTK, GHS-J, and NLM Toxnet all listed the substance as a suspected mutagen. When considering all of the evidence, the substance was classified as a suspected mutagen for safety reason. Reference: NLM CCRIS (2011) and GHS-J (2006).
--------------	---

- **Potential Health Effect(s):** Suspected of causing genetic defects.

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Print Date 11/22/2016

Revision Date 11/22/2016

Trade Name: EP11HT GRAY A

(Contd. of page 7)

Carcinogenicity

25068-38-6 Bisphenol-A-(epichlorohydrin) epoxy resin

Carcinogenicity negative (Test species: n/a) (Not listed by ACGIH, IARC, NTP, or OSHA)
(Mouse)
1 out of 4 cases with female mice showed positive carcinogenic results after a repeated dermal application with 10% concentration of the substance for two years. When considering all of the evidence, the substance was not classified as a carcinogen.

1317-65-3 Calcium Carbonate

Carcinogenicity negative (salmonella typhimurium) (Preincubation)
In Vitro - Negative with and without metabolic activation.
Reference: NLM TOXNET of CAS No. 471-34-1 (2010).

67762-90-7 Siloxanes and Silicones, di-Me, reaction products with silica

Carcinogenicity (Test species: n/a) (Not listed by IARC, NTP, OSHA or ACGIH)

2426-08-6 Butylglycidylether

Carcinogenicity (dynamic) N/A (Test species: n/a)
The substance is not listed as a carcinogen by IARC, OSHA or NTP.

Potential Health Effect(s): Not a known Carcinogen.

Reproductive Toxicity

25068-38-6 Bisphenol-A-(epichlorohydrin) epoxy resin

Reproductive Toxi. negative (Test species: n/a) (no reproductive or developmental effect observed)
There was no reproductive or developmental effect observed at dosing levels that were toxic to parental animals.
Reference: GHS-J (2006).

1317-65-3 Calcium Carbonate

Reproductive Toxi. (rat)
Up to 1.25% diet of the substance for 6 weeks prior to mating and during gestation and found no adverse effects.
Reference: ACToR of CAS No. 471-34-1 (2010).

67762-90-7 Siloxanes and Silicones, di-Me, reaction products with silica

Reproductive Toxi. (No data available)

2426-08-6 Butylglycidylether

Reproductive Toxi. Positive (Test species: n/a) (A known chemical to reproductive males)
The substance was a listed chemical to male reproductive toxicity by California Proposition 65.
Suspected of causing genetic defects. Royce SDS 2014.

Specific Target Organ Toxicity - Single Exposure

25068-38-6 Bisphenol-A-(epichlorohydrin) epoxy resin

STOT-Single Target: None (Rats and Mice) (No effect after single oral doses)
Somnolence (general depressed activity) and dyspnea were observed after a single oral application with 11400 mg/kg to rats, or 15600 mg/kg to mice of the substance. However, the dose levels were both outside of the guidance value ranges.
Reference: NLM Toxnet (2010).

1317-65-3 Calcium Carbonate

STOT-Single (Human)
Inhalation 0.005 mg/L for 3 hours:
target organs - systemic toxicity
May affect nasal function and cause nasal symptoms.

Ingested up to 15g of the substance:
target organs - systemic toxicity
Symptoms included: fatigue, anorexia, nausea and vomiting, an elevated blood pressure, hemoconcentration, leukocytosis, metabolic alkalosis, elevated body weight and hypokalemia.
Reference: ACToR of CAS No. 471-34-1 (2010).

(rat)
Exposed to 0.0812 mg/L for 90 minutes/ after 21 hr. No effect on lung weight, macrophage concentration, or histopathology.
Reference: ACToR of CAS No. 471-34-1 (2010).

67762-90-7 Siloxanes and Silicones, di-Me, reaction products with silica

STOT-Single (dynamic) (No data available)

2426-08-6 Butylglycidylether

STOT-Single (mouse) (Respiratory tract irritation via Inhalation)
Target Organs: Respiratory tract irritation (Category 3)
Inhalation with 260 mg/m³ of the substance caused somnolence, dyspnea, and respiratory depression in mice.
Reference: NLM Toxnet (2011) and ESIS CLP/GHS.

Potential Health Effect(s): No further relevant information; classification is not possible.

Specific Target Organ Toxicity - Repeated Exposure

25068-38-6 Bisphenol-A-(epichlorohydrin) epoxy resin

STOT-Repeated Target: N/A (guinea pig) (insufficient data for classification)
With dermal application of the substance for 55 days, increased seromucoid concentrations, decreased lactate-dehydrogenase (LDH), and decreased leucynaphthylamidase (LNA) were observed in the test animals. Meanwhile, the substance caused a toxic effect on blood components of female guinea-pigs with greater effects on pregnant animals. However, there was no detail available regarding the dose level or test guideline, classification was thus not possible.
Reference: HSNO CCID (2010).

(Contd. on page 9)

US

Safety Data Sheet

acc. to OSHA HCS

Print Date 11/22/2016

Revision Date 11/22/2016

Trade Name: EP11HT GRAY A

(Contd. of page 8)

1317-65-3 Calcium Carbonate

STOT-Repeated

(Human)

Target organs - Systemic toxicity

Symptoms: Infrequent instances of hypercalcemia with alkalosis, calcinosis, azotemia, renal dysfunction, GI hemorrhage and vomiting or aspiration through nasogastric tube seem to predispose to the disorder.

Reference: ACToR of CAS No. 471-34-1.

67762-90-7 Siloxanes and Silicones, di-Me, reaction products with silica

STOT-Repeated

(No data available)

2426-08-6 Butylglycidylether

STOT-Repeated

(Test species: n/a) (Insufficient data for classification)

NOAEL (Inhalation) = 0.52 mg/L/day.

1. Rats - Decreased body fat, thymic size, and lymphoid organs; abdominal and thoracic viscera; evidence of pneumonia and lethargy; emaciation; liver necrosis; significant increase in kidney/body and lung/body weight ratios; and high incidence of testicular atrophy and bronchopneumonia.

2. Rabbits - Decreased liver weights; decreased body fat and fecal material in GI tract; exudative rhinitis; and lethargy.

3. Mice - Decreased liver weights; decreases body fat, thymic size and lymphoid organs; postural and gait changes.

No test method available; meanwhile, EU or HMIS didn't classify the substance as a chronic hazard. Without further information, classification is not possible.

Reference: HPVIS (2011) and HSDB (2011).

Aspiration Hazard
25068-38-6 Bisphenol-A-(epichlorohydrin) epoxy resin

Aspiration Hazard

(No data available)

1317-65-3 Calcium Carbonate

Aspiration Hazard

No data available.

67762-90-7 Siloxanes and Silicones, di-Me, reaction products with silica

Aspiration Hazard

(No data available)

2426-08-6 Butylglycidylether

Aspiration Hazard

(No data available)

Potential Health Effect(s): No relevant information; classification is not possible.

Additional Information No further relevant information.

12 Ecological information

Aquatic Environmental Toxicity
25068-38-6 Bisphenol-A-(epichlorohydrin) epoxy resin

Algae Toxicity

(No data available)

Crustacean Toxicity

1.4 - 1.7 mg/l (Daphnia magna (water flea)) (EC50 (48 hrs))

Fish Toxicity

1.41 mg/l (Oryzias latipes (Rice fish)) (LC50 (96 hrs))

3.1 mg/l (Pimephales promelas (fathead minnow)) (LC50 (96 hrs))

Based on the non-rapid degradability and the acute LC50 < 10 mg/L, the substance is classified as a Chronic-2 environmental hazard.

Reference: CHRIP (2010).

1317-65-3 Calcium Carbonate

Algae Toxicity (static)

56000 mg/l (Gambusia affinis (western mosquitofish)) (LC50 (24 - 96 hrs))

Reference: ACToR of CAS No. 471-34-1 (2010).

(Poecilia Latipinna (Sailfin molly))

Exposure period: 96 hrs.

NOEC > 200 mg/L

Reference: IUCLID Dataset of CAS No. 471-34-1 (2000).

Crustacean Toxicity

The substance is not toxic to aquatic organisms.

Reference: Canada DSL of CAS No. 471-34-1 (2007).

Fish Toxicity

The substance is not toxic to aquatic organisms.

Reference: Canada DSL of CAS No. 471-34-1 (2007).

Micro-organism toxi

The substance is not toxic to aquatic organisms.

Reference: Canada DSL of CAS No. 471-34-1 (2007).

67762-90-7 Siloxanes and Silicones, di-Me, reaction products with silica

Algae Toxicity

> 10000 mg/l (Scenedesmus subspicatus) (ErC50 (24 hrs), OECD 201)

Crustacean Toxicity

> 1000 mg/l (Daphnia magna (water flea)) (EC50 (24 hrs), OECD 202)

Fish Toxicity

> 10000 mg/l (Brachydanio rerio (Zebra fish)) (LC50 (96 hrs), OECD 203)

Reference: Cabot (M)SDS (2012).

2426-08-6 Butylglycidylether

Algae Toxicity

35 mg/l (Selenastrum capricornum) (LC50 (96 hrs); OECD TG 201)

Crustacean Toxicity

3.9 mg/l (Daphnia magna (water flea)) (EC50 (48 hrs); OECD TG 202)

Based on the acute EC50 < 10 mg/L and the rapid degradability, the substance is classified as a Chronic-3 environmental hazard.

Reference: HPVIS (2011)

Fish Toxicity

(No data available)

Aquatic Environmental Toxicity Assessment: No further relevant information; classification is not possible.

(Contd. on page 10)

US

Safety Data Sheet acc. to OSHA HCS

Print Date 11/22/2016

Revision Date 11/22/2016

Trade Name: EP11HT GRAY A

(Contd. of page 9)

Degradability and Stability

25068-38-6 Bisphenol-A-(epichlorohydrin) epoxy resin

Biodegradation	non-biodegrad. (Test species: n/a) (Biodegradation (OECD TG 302B; 28 days) = 12%) (Activated Sludge) (OECD TG 301C; 4 weeks; Conc. 100 mg/L) Biodegradation (Indirect Analysis from BOD) = 0% Biodegradation (Direct Analysis from HPLC) = 0% The substance is non-biodegradable. Reference: CHRIP (2010).
Persistence	(Test species: n/a) (This substance is persistent) Reference: Canada DSL (2007) and CHRIP (2010).
Photodegradation	6.69E-11 cm ³ /molecule-sec (OH radical) (Half-life (T1/2) = 1.92 hrs) However, photolysis in water is negligible.
Stability in water	(No data available)

1317-65-3 Calcium Carbonate

Biodegradation	The test is not applicable since this substance is inorganic and not soluble in water. Reference: IUCLID Dataset of CAS No. 471-34-1 (2000).
Photodegradation	positive cm ³ /molecule-sec The substance is persistent. Reference: ACToR of CAS No. 471-34-1 (2010).
Stability in water	No data available.

67762-90-7 Siloxanes and Silicones, di-Me, reaction products with silica

Biodegradation	(No data available)
Persistence	(Test species: n/a) (The substance is not persistent) Reference: Canada DSL (2007).
Photodegradation	(No data available)
Stability in water	(No data available)

2426-08-6 Butylglycidylether

Biodegradation	readily biodeg. (Test species: n/a) (Biodegradation (OECD TG 301C) ≥ 40%) Biodegradation (Direct Analysis from TOC and GC; 28 days) = 56% and 68% Biodegradation (Indirect Analysis from BOD; 28 days) = 40% The substance is readily biodegradable. Reference: CHRIP (2011).
Persistence	(Test species: n/a) (The substance is not persistent) Reference: Canada DSL (2007).
Photodegradation	1.99E-11 cm ³ /molecule-sec (Test species: n/a) Half-life (1.5E6 OH/cm ³ ; calculated by EPIWIN program) = 6.47 hours Reference: NLM Toxnet (2011) and HPVIS (2011).
Stability in water	stable (Test species: n/a) (Half-life (OECD TG 111; PH=7) = 486.7 hours) Thus, the substance is hydrolytically stable in the aquatic environment. Reference: HPVIS (2011).

Bioaccumulation and Distribution

25068-38-6 Bisphenol-A-(epichlorohydrin) epoxy resin

LogPow	3.7 - 3.9 (Test species: n/a)
BCF	0.56-42 (Cyprinus carpio) (The substance is low-bioaccumulative) BCF (28 days; Concentration: 10 µg/L) = 0.56 - 0.67, 3.3 - 4.2 BCF (28 days; Concentration: 1 µg/L) = 5.6 - 6.8, 33 - 42 Reference: CHRIP (2010).
Koc	1800 - 4400 L/kg (soil) Potential for mobility in soil is moderate.

1317-65-3 Calcium Carbonate

LogPow	No data available.
BCF	No data available.
Koc	No data available.
Environment fate	No data available.

67762-90-7 Siloxanes and Silicones, di-Me, reaction products with silica

LogPow	(No data available)
BCF	(No data available) (The substance is not bioaccumulative) Reference: Canada DSL CCR (2011).
Koc	(No data available)

2426-08-6 Butylglycidylether

LogPow	0.63 (Test species: n/a) Reference: NLM Toxnet (2011).
BCF	3.16 (Test species: n/a) (The substance is not bioaccumulative) Reference: Canada DSL (2007) and CCR (2011).
Koc	(No data available)

Degradability and Bioaccumulation Assessment: Non-rapidly degradable, and low bioaccumulative.

(Contd. on page 11)

Safety Data Sheet acc. to OSHA HCS

Print Date 11/22/2016

Revision Date 11/22/2016

Trade Name: EP11HT GRAY A

(Contd. of page 10)

Additional Information No further relevant information.

13 Disposal considerations

Hazardous Waste List

Description: It may be necessary to contain and dispose of the substance/mixture as a hazardous waste.

RCRA Waste:

2426-08-6 Butylglycidylether

D001 2.5-5%

Waste Treatment Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Generation of waste should be avoided or minimized wherever possible.

Chemical waste, even small quantities, is neither allowed to be poured down drains, sewage system or waterways; nor disposed with household garbage.

Dispose of contents/containers in accordance with local, regional, national, and international regulations.

Unused and Uncontaminated Packagings

Recommendation Dispose of according to your local waste regulations.

14 Transport information

UN-Number

DOT, ADR, IMDG, IATA

UN3082

UN Proper Shipping Name

DOT

Environmentally hazardous substances, liquid, n.o.s. (Bisphenol-A-(epichlorohydrin) epoxy resin)

IMDG

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol-A-(epichlorohydrin) epoxy resin), MARINE POLLUTANT

IATA

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol-A-(epichlorohydrin) epoxy resin)

Transport hazard class(es)

DOT, IMDG, IATA



Class Label

9 Miscellaneous dangerous substances and articles

ADR



Class Label

9 (M6) Miscellaneous dangerous substances and articles

Packing group

DOT, ADR, IMDG, IATA

III

Environmental Hazards:

Marine Pollutant:

Yes

Special Marking (ADR):

Symbol (fish and tree)

Special Marking (IATA):

Symbol (fish and tree)

Symbol (fish and tree)

Special Precautions:

Danger Code (Kemler):

Warning: Miscellaneous dangerous substances and articles

EMS Number:

90

Stowage Category

F-A

A

Transport in Bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

Transport/Additional Information:

DOT

Quantity limitations

On passenger aircraft/rail:

On cargo aircraft only:

Not regulated by DOT in packages of 5L or less.

Special marking with the symbol (fish and tree).

ADR

Excepted quantities (EQ)

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

(Contd. on page 12)

Safety Data Sheet acc. to OSHA HCS

Print Date 11/22/2016

Revision Date 11/22/2016

Trade Name: EP11HT GRAY A

(Contd. of page 11)

· IMDG

- Limited quantities (LQ)
- Excepted quantities (EQ)

5L

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· UN "Model Regulation":

UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S. (BISPHENOL-A-(EPICHLOROHYDRIN) EPOXY RESIN), 9, III

15 Regulatory information

· USA Regulation Lists
· SARA (Superfund Amendments and Reauthorization Act of 1986)
· Section 302 (Extremely Hazardous Substances)

None of the ingredients is listed.

· Section 313 (Toxics Release Inventory (TRI) reporting)

None of the ingredients is listed.

· Section 311/312 (Hazardous Chemical Inventory Reporting)

25068-38-6	Bisphenol-A-(epichlorohydrin) epoxy resin	A, C	70-80%
1317-65-3	Calcium Carbonate	A, C	10-20%
2426-08-6	Butylglycidylether	A, C, F	2.5-5%
1333-86-4	Carbon black	A, C	0-<0.1%

· Hazard Abbreviations for SARA 311/312

A - Acute Health Hazard

C - Chronic Health Hazard

F - Fire Hazard

R - Reactive Hazard

S - Sudden Release of Pressure Hazard

· TSCA (Toxic Substances Control Act)

All ingredients are listed.

· Proposition 65
· Chemicals Known to Cause Cancer

This product may also contain extremely small amounts of one or more naturally occurring materials known to the State of California to cause cancer, birth defects or other reproductive harm.

1333-86-4	Carbon black	
106-89-8	1-chloro-2,3-epoxypropane	

· Chemicals Known to Cause Reproductive Toxicity for Females

None of the ingredients is listed.

· Chemicals Known to Cause Reproductive Toxicity for Males

106-89-8	1-chloro-2,3-epoxypropane	
----------	---------------------------	--

· Chemicals Known to Cause Developmental Toxicity

None of the ingredients is listed.

· Carcinogenic Categories
· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· IARC (International Agency for Research on Cancer)

1333-86-4	Carbon black	2B
-----------	--------------	----

· NTP (National Toxicology Program)

None of the ingredients is listed.

· TLV (Threshold Limit Value Established by ACGIH)

1333-86-4	Carbon black	A4
-----------	--------------	----

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· International Regulation Lists
· Chinese Chemical Inventory of Existing Chemical Substances:

All ingredients are listed.

· Japanese Existing and New Chemical Substance List:

All ingredients are listed.

· Korean Existing Chemical Inventory:

All ingredients are listed.

· European Pre-registered substances:

All ingredients are listed.

· REACH - Substances of Very High Concern (SVHC) List:

None of the ingredients is listed.

· Restriction of Hazardous Substances Directive (RoHS) list:

None of the ingredients is listed.

US

(Contd. on page 13)

Safety Data Sheet acc. to OSHA HCS

Print Date 11/22/2016

Revision Date 11/22/2016

Trade Name: EP11HT GRAY A

(Contd. of page 12)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department Issuing (M)SDS:** Product Safety Department

· **Contact:** msds@resinlab.com

· **Abbreviations and acronyms:**

ACGIH: American Conference of Governmental Industrial Hygienists
 ACToR: US EPA Aggregated Computational Toxicology Resource
 ADR: European Agreement Concerning the International Carriage of Dangerous Goods by Road
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 CCR: Canadian Categorization Results
 CCRIS: US NLM TOXNET Chemical Carcinogenesis Research Information System
 CHRIP: Japan NITE Information on Biodegradation and Bioconcentration of the Existing Chemical Substances in the Chemical Risk Information Platform
 ChV: Chronic Value
 DOT: US Department of Transportation
 DSL: Canada Domestic Substance List
 ECHA: European Chemicals Agency's Dissemination portal with information on chemical substances registered under REACH
 HMIS: US National Paint & Coatings Association (NPCA) Hazardous Materials Identification System
 HPVIS: US EPA High Production Volume Information System
 HSDB: US NLM TOXNET Hazardous Substances Databank
 HSNO CCID: New Zealand Hazardous Substances and New Organisms Chemical Classification Information Database
 IARC: International Agency for Research on Cancer developed by United Nations World Health Organisation (WHO)
 IATA-DGR: Dangerous Goods Regulations (DGR) by the International Air Transport Association (IATA)
 ICAO-TI: Technical Instructions (TI) by the International Civil Aviation Organization (ICAO)
 ICSC: International Chemical Safety Cards
 IMDG: International Maritime Dangerous Goods; the principal international rules for International Carriage of Dangerous Goods by SEA under the Recommendations on the Transport of Dangerous Goods by United Nations (RTDG)
 IUCLID: EU REACH International Uniform Chemical Information Database
 LC50/LD50: Lethal Concentration/Dose, 50 percent
 N/a: Not available or Not applicable
 NFPA: US National Fire Protection Association
 NIOSH: US National Institute of Occupational Safety and Health
 NITE: National Institute of Technology and Evaluation, Japan
 NLM TOXNET: US National Library of Medicine Toxicology Data Network
 OECD: Organisation for Economic Co-operation and Development
 OSHA: US Occupational Safety and Health Administration
 P: Marine Pollutant
 RCRA: Resource Conservation and Recovery Act (USA)
 REACH: EU Registry, Evaluation and Authorisation of Chemicals
 RID: the Regulations Concerning the International Carriage of Dangerous Goods by Rail; published by the Central Office for International Carriage by Rail (OTIF)
 RTDG: the Recommendations on the Transport of Dangerous Goods by United Nations (UN)
 RTECS: US Registry of Toxic Effects of Chemical Substances
 SARA: US Superfund Amendments and Reauthorization Act
 SIDS: OECD existing chemicals Screening Information Data Sets
 TEEL: Temporary Emergency Exposure Limit developed by US Subcommittee on Consequence Assessment and Protective Actions (SCAPA) of US Department of Energy (DOE)
 TOXLINE: US NLM bibliographic database search system
 TSCA: US Toxic Substance Control Act
 BCF: Bioconcentration Factor
 ESIS: European Chemical Substances Information System
 Koc: Partition coefficient, soil Organic Carbon to water
 SVHC: EU ECHA Substance of Very High Concern
 · **Date of preparation / last revision** 11/22/2016 / 4

US