

Printing date 10/17/2018 Reviewed on 05/17/2018

1 Identification

- · Product identifier
 - · Trade name: EP1112NC Black A · Recommended use Epoxy Resin · Restrictions on use For industrial use only

· Details of the supplier of the safety data sheet Manufacturer/Supplier:

Manufacturer/Supplier:
ResinLab, LLC
N109 W13300 Ellsworth Drive
Germantown, WI 53022
1-877-259-1669
www.resinlab.com
Information Department: Product Safety Department: msds@resinlab.com
Emergency Telephone Number:
North America - Chemtrec: 1-800-424-9300 (24 hours)
International - Chemtrec: 01-703-527-3887 (24 hours)

2 Hazard(s) identification

Classification of the substance or mixture

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

H341 Suspected of causing genetic defects.

· Label elements

GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). Hazard pictograms





GHS07

GHS08

· Signal word Warning

Hazard-determining components of labeling:

Bisphenol-A-(epichlorohydrin) epoxy resin o-Cresyl glycidyl ether Hazard statements

Hazard statements
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H319 Causes an allergic skin reaction.
H341 Suspected of causing genetic defects.
Precautionary statements
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Avoid breathing dust/fume/gas/mist/vapors/spray
Wash thoroughly after handling.
Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves/protective clothing/eye protection/face protection.
If on skin: Wash with plenty of water.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
IF exposed or concerned: Get medical advice/attention.
If skin irritation or rash occurs: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.
Wash contaminated clothing before reuse.

Wash contaminated clothing before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Classification system: NFPA System NFPA ratings (scale 0 - 4)



Health = 2 Reactivity = 0

NFPA special hazards (water reactivity and oxidizing property): None

· HMIS System · HMIS-ratings (scale 0 - 4)



Health = 2Fire = 1 Reactivity = 0

Other hazards

rer riazarus Results of PBT and vPvB assessment · PBT: Not applicable. · vPvB: Not applicable.



Printing date 10/17/2018 Reviewed on 05/17/2018

Trade name: EP1112NC Black A

(Contd. of page 1)

3 Composition/information on ingredients

· Chemical characterization: Mixtures

 Dangerous components 		
CAS: 25068-38-6	Bisphenol-A-(epichlorohydrin) epoxy resin	70-80%
NLP: 500-033-5	Aquatic Chronic 2, H411 Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317	
CAS: 2210-79-9	o-Cresyl glycidyl ether	10-20%
EINECS: 218-645-3	Muta. 2, H341	
Index number: 603-056-00-X		
RTECS: TZ3700000	Skin Irrit. 2, H315, Skin Sens. 1, H317	
CAS: 1333-86-4	Carbon black	0.1-1%
EINECS: 215-609-9		
RTECS: FF5800000		

Additional information:

If the chemical name/CAS number is proprietary and or weight percentage is listed as a range, the specific chemical identity and or percentage of composition has been withheld as a trade secret.

4 First-aid measures

Description of first aid measures
General information: Keep warm, position comfortably and cover well.

After inhalation:

Remove victim from exposure to fresh air. Keep person at rest. Provide oxygen if person is not breathing. Supply fresh air and if symptoms occur call for a doctor. In case of unconsciousness place patient stably in side position for transportation.

After skin contact:

Immediately wash with water and soap and rinse thoroughly. Remove all contaminated clothing and wash before reuse.

If skin rash or irritation occurs, seek medical advice.

After eye contact:
Immediately flush opened eyes with water for 5 minutes, then remove contact lenses if present, continue flushing for at least another 15

If symptoms develop seek medical attention.

After swallowing:

If victim is unconscious; never give anything by mouth. If victim is conscious, rinse out mouth with water. Get medical attention if you feel unwell.

Information for doctor:

Most important symptoms and effects, both acute and delayed No further relevant information available.

Indication of any immediate medical attention and special treatment needed

Check section 11 Toxicological Information for further relevant information.

5 Fire-fighting measures

Extinguishing media

Suitable extinguishing agents: Use fire fighting measures that suit the environment.

Alcohol resistant foam Carbon dioxide dry chemical Water spray

Special hazards arising from the substance or mixture Will not burn unless preheated. In case of fire, the following can be released:

Aldehydes Phenolics

Carbon dioxide (CO) and Carbon monoxide (CO)

Advice for firefighters

Protective equipment:
If employees are expected to fight fires, they must be trained and equipped as stated in the OSHA fire brigades standard (29 CFR 1910.156).

As with any fire, wear positive-pressure self-contained breathing apparatus and full protective gear that are NIOSH approved.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear protective clothing.

Do not breathe gas, vapors, dusts or mists if their inhalable particles occur during use.

Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up:

For large spills: provide diking or containment to minimize spreading. If possible pump and store material in appropriate container. For small spills: Ventilate and wash area. Collect spills and absorbant material in appropriate container. Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

(Contd. on page 3)





Printing date 10/17/2018 Reviewed on 05/17/2018

Trade name: EP1112NC Black A

Dispose contaminated material as waste according to item 13.

(Contd. of page 2)

7 Handling and storage

Handling:
Precautions for safe handling
Do not breathe dust created by sanding, cutting, machining or grinding.
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.

Keep away from incompatible material(s).

Keep away from incompatible material(s). Avoid any release into the environment. Do not breathe dust/fumes/mist/vapor/spray.

Avoid contact with eyes, skin and clothing. Keep away from heat,sparks, flames and ignition sources. Observe all the personal protection requirements in Section 8.

· Conditions for safe storage, including any incompatibilities

Requirements to be met by storerooms and receptacles:

Provide ventilation for receptacles.

Keep stored in accordance with local, regional, national, and international regulations.

8 Exposure controls/personal protection

Control parameters

Components with limit values that require monitoring at the workplace:

1333-86-4 Carbon black

PEL Long-term value: 3.5 mg/m3

REL Long-term value: 3.5* mg/m³
*0.1 in presence of PAHs;See Pocket Guide Apps.A+C

Long-term value: 3* mg/m³

*inhalable fraction

· Additional Occupational Exposure Limit Values for possible hazards during processing: None.

If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits.

If exposure limits have not been established, maintain airborne levels to an acceptable level.

Personal protective equipment:

General protective equipment:
General protective and hygienic measures:
Be sure to clean skin thoroughly after work and before breaks.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Avoid contact with the eyes and skin.

Personal Protective Equipment (PPE)

Breathing equipment: Sufficient ventilation in pattern and volume should be provided in order to maintain air contaminant levels below recommended

Use a NIOSH approved air-purifying organic vapor respirator if occupational limits are exceeded. For emergency situations, confined space use, or other conditions where exposure limits may be greatly exceeded, use an approved air supplied respirator. Observe OSHA regulations (29CFR 1910.134) for respirator use.

Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

ection of the glove material on consideration of the penetration times, rates of diffusion and the degradation Material of gloves



Chemical resistant gloves

· Eye protection:



Safety Glasses with side shields

Body protection: Appropriate chemical resistant clothing.
Limitation and supervision of exposure into the environment
The Engineering measures or controls, and PPE recommendations are only guidelines and may not apply to every situation. For additional information, please consult the corresponding requirements under OSHA 29 CFR 1910.94-95, and 29 CFR 1910.132-138.

(Contd. on page 4)



Printing date 10/17/2018 Reviewed on 05/17/2018

Trade name: EP1112NC Black A

(Contd. of page 3)

9 Physical and chemical propertion	es
Information on basic physical and chen General Information Appearance:	nical properties
Form:	Liquid
: Color:	Black
· Odor: · Odor threshold:	Mild epoxy odor Not determined
· pH-value:	Not determined.
Change in condition Melting point/Melting range: Boiling point/Boiling range:	Undetermined. Undetermined.
· Flash point:	>113 °C (>235.4 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	Not determined.
· Decomposition temperature:	Not determined.
· Auto igniting:	Not determined.
· Danger of explosion:	Product does not present an explosion hazard.
Explosion limits: Lower: Upper:	Not determined. Not determined.
Vapor pressure: Vapor Density:	Not determined. not determined
Density at 20 °C (68 °F): Relative density Vapor density Evaporation rate	1.12 g/cm³ (9.35 lbs/gal) Not determined. Not determined. Not determined.
Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/wate	r): Not determined.
Viscosity: Dynamic at 20 °C (68 °F): Kinematic: VOC content:	1,200 mPas Not available. 0.00 % 0.0 g/l / 0.00 lb/gal

10 Stability and reactivity

- · Reactivity Not a regulated physical hazard under GHS.
- Hazardous Reactivity and Chemical Stability Stable under normal conditions of use, storage and temperatures.
 Thermal decomposition / conditions to be avoided:
 To avoid thermal decomposition do not overheat.
 No decomposition if used and stored according to specifications.

 Possibility of hazardous reactions In contact with incompatible materials.

 Conditions to avoid Keep away from heat, sparks, flame and any other ignition sources.

 Incompatible materials:

Incompatible materials:
Oxidizing agents
Mercaptans
Acids

Amines Bases (Alkalis)

Hazardous decomposition products: Possible in traces. Refer to section 5.

11 Toxicological information

· Information on toxicological effects · Acute toxicity:

· LD/LC50 values that are relevant for classification:

25068-38-6 Bisphenol-A-(epichlorohydrin) epoxy resin

11,400 mg/kg (rat) Oral 1 D50

LD50 20,000 mg/kg (rabbit) (Test guideline not available) Dermal

Inhalative LC50/4 h mg/l (Test species: n/a) (Toxicity not expected based on the acute oral data)

2210-79-9 o-Cresyl glycidyl ether

LD50 4,000 mg/kg (rat) Dermal LD50 >2,000 mg/kg (rabbit)

Inhalative LC50/4 h mg/l (rat) (Non-toxic; LC50 exceeded the satured vapor value)

- Primary irritant effect:
 on the skin: Irritant to skin and mucous membranes.
 on the eye: Irritating effect.

(Contd. on page 5)



Printing date 10/17/2018 Reviewed on 05/17/2018

Trade name: EP1112NC Black A

(Contd. of page 4)

· Sensitization: Sensitization possible through skin contact.

Additional toxicological information:
The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

Carcinogenic categories

IARC (International Agency for Research on Cancer)

1333-86-4 Carbon black

2B

NTP (National Toxicology Program)

None of the ingredients is listed.

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

Persistence and degradability No further relevant information available.
 Other information: The product is easily biodegradable.
 Behavior in environmental systems:
 Bioaccumulative potential No data available.
 Mobility in soil No further relevant information available.
 Additional ecological information: The product is non-resid degradable.

Additional ecological information: The product is non-rapid degradable, and low or not highly bioaccumulative. General notes:

General notes:
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Results of PBT and vPvB assessment
PBT: None of the ingredients is listed.
vPvB: None of the ingredients is listed.
Other adverse effects No further relevant information available.

13 Disposal considerations

Waste treatment methods

Recommendation:Must be specially treated adhering to official regulations.
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Uncleaned packagings

Recommendation: Dispose of according to your local waste regulations.

· UN-Number	
· DOT	Not regulated in packages less than 5L.
· IMDG, IATA	UN3082
UN proper shipping name	
DOT	not regulated
· IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUI
	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUI. N.O.S. (Bisphenol-A-(epichlorohydrin) epoxy resin, o-Cres glycidyl ether), MARINE POLLUTANT
· IATA	ENVIRONMENTALLY HAZARDOUS SUBSTANCE. LIQUI
	ENVÍRONMENTALLY HAZARDOUS SUBSTANCE, LIQUI. N.O.S. (Bisphenol-A-(epichlorohydrin) epoxy resin, o-Cres
	glycidyl ether)
Transport hazard class(es)	
· DOT	
· Class	Not regulated in packages less than 5L.
¥2>	
· Class · Label	9 Miscellaneous dangerous substances and articles 9
· Packing group	
·DOT	Not regulated in packages less than 5L.
IMDG, IATA	
Environmental hazards:	Product contains environmentally hazardous substances: Bisphene A-(epichlorohydrin) epoxy resin
Special precautions for user	Warning: Miscellaneous dangerous substances and articles
Danger code (Kemler): EMS Number:	90
· Stowage Category	F-A,S-F A
otoriuge outegory	/1



Printing date 10/17/2018 Reviewed on 05/17/2018

Trade name: EP1112NC Black A

(Contd. of page 5) Transport in bulk according to Annex II of MARPOL73/78 and the Not applicable Transport/Additional information: **IMDG** Limited quantities (LQ) Excepted quantities (EQ) Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml · UN "Model Regulation":

UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S. (BISPHENOL-A-(EPICHLOROHYDRIN) EPOXY RESIN, O-CRESYL GLYCIDYL ETHER), 9, III 15 Regulatory information · Safety, health and environmental regulations/legislation specific for the substance or mixture SARA Section 355 (extremely hazardous substances): None of the ingredients is listed. SARA Section 313 (Specific toxic chemical listings): None of the ingredients is listed. · Section 311/312 (Hazardous Chemical Inventory reporting) · SARA Section 311/312 (Hazardous Chemical Inventory Reporting) 25068-38-6 Bisphenol-A-(epichlorohydrin) epoxy resin A, C 70-80% 2210-79-9 o-Cresyl glycidyl ether A, C 10-20% A, C 0.1-1% 1333-86-4 Carbon black Hazard Abbreviations for SARA 311/312 A - Acute Health Hazard C - Chronic Health Hazard - Fire Hazard R - Reactive Hazard S - Sudden Release of Pressure Hazard TSCA 8 (b) Inventory: All ingredients are listed TSCA new (21st Century Act) 25068-38-6 Bisphenol-A-(epichlorohydrin) epoxy resin ACTIVE/EXEMPT 2210-79-9 o-Cresyl glycidyl ether ACTIVE/EXEMPT 1333-86-4 Carbon black ACTIVE/EXEMPT Proposition 65 Chemicals known to cause cancer: 1333-86-4 Carbon black · Chemicals known to cause reproductive toxicity for females: None of the ingredients is listed. Chemicals known to cause reproductive toxicity for males: None of the ingredients is listed. Chemicals known to cause developmental toxicity: None of the ingredients is listed. Carcinogenic categories · EPA (Environmental Protection Agency) None of the ingredients is listed. TLV (Threshold Limit Value established by ACGIH) 1333-86-4 Carbon black A4 · NIOSH-Ca (National Institute for Occupational Safety and Health) None of the ingredients is listed. International Regulation Lists GHS label elements GHS label elements REACh - Substances of Very High Concern (SVHC) List: None of the ingredients is listed. Restriction of Hazardous Substances Directive (RoHS) list: None of the ingredients is listed.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Department Issuing (M)SDS: Product Development Department

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

Contact: msds@resinlab.com
 Date of preparation / last revision 10/17/2018 / 2
 * Data compared to the previous version altered.