

Safety Data Sheet
acc. to OSHA HCS

Print Date 05/12/2015

Revision Date 05/12/2015

Product Identifier

- **Trade Name:** EP1056LV BLACK A
- **Application of the Substance or Mixture:** Epoxy Resin

Details of the Supplier of the Safety Data Sheet (SDS)

- **Manufacturer or Supplier:**
Resinlab, LLC
N109 W13300 Ellsworth Drive,
Germantown, WI 53022
1-800-388-8605
www.resinlab.com
- **Information Department:** Product Safety Department: msds@resinlab.com
- **Emergency Telephone Number:**
North America - Chemtrec: 1-800-424-9300 (24 hours)
International - Chemtrec: 01-703-527-3887 (24 hours)

2 Hazard(s) identification

Hazard Classification



GHS09 Environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2A H319 Causes serious eye irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.

Label Elements

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

Pictogram(s)



GHS07 GHS09

· **Signal Word** Warning

Hazard-determining Component(s)

Bisphenol-A-(epichlorohydrin) epoxy resin
1, 2, 3-Propanetriyl ester of 12-(oxiranylmethoxy)-9-octadecanoic acid

Hazard statements

Causes skin irritation.
Causes serious eye irritation.
May cause an allergic skin reaction.
Toxic to aquatic life with long lasting effects.

Precautionary statements

Avoid breathing dust/fume/gas/mist/vapors/spray
Wear protective gloves.
Wear eye protection / face protection.
Avoid release to the environment.
Wash thoroughly after handling.
Contaminated work clothing must not be allowed out of the workplace.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Specific treatment (see on this label).
Wash contaminated clothing before reuse.
If skin irritation or rash occurs: Get medical advice/attention.

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Print Date 05/12/2015

Revision Date 05/12/2015

Trade Name: EP1056LV BLACK A

(Contd. of page 1)

If eye irritation persists: Get medical advice/attention.
 If on skin: Wash with plenty of water.
 Collect spillage.
 Take off contaminated clothing and wash it before reuse.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

Prevention

Avoid breathing dust/fume/gas/mist/vapors/spray
 Wear protective gloves/protective clothing/eye protection/face protection.
 Avoid release to the environment.
 Wash thoroughly after handling.
 Contaminated work clothing must not be allowed out of the workplace.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard Rating System

NFPA System

NFPA Ratings (scale 0 - 4)



NFPA special hazards (water reactivity and oxidizing property): None

HMIS System

HMIS Ratings (scale 0 - 4)



Other hazards

Results of PBT and vPvB assessment




PBT: Not applicable.

vPvB: Not applicable.

3 Composition/information on ingredients

Chemical Characterization: Mixtures

Composition/Information on Ingredients

CAS: 25068-38-6 NLP: 500-033-5 Index Number: 603-074-00-8	Bisphenol-A-(epichlorohydrin) epoxy resin 	60-70%
CAS: 74398-71-3 EC number: 616-085-8	1, 2, 3-Propanetriyl ester of 12-(oxiranylmethoxy)-9-octadecanoic acid 	10-20%
CAS: 1317-65-3 EINECS: 215-279-6 RTECS: EV 9580000	Calcium Carbonate	10-20%
CAS: 67762-90-7 EC number: 614-122-2	Siloxanes and Silicones, di-Me, reaction products with silica	0.1-<1%
CAS: 1333-86-4 EINECS: 215-609-9 RTECS: FF5800000	Carbon black	0.1-<1%
CAS: 14808-60-7 EINECS: 238-878-4 RTECS: VV 7330000	Quartz 	0-<0.1%

(Contd. on page 3)

Safety Data Sheet acc. to OSHA HCS

Print Date 05/12/2015

Revision Date 05/12/2015

Trade Name: EP1056LV BLACK A

(Contd. of page 2)

Classification System:

The Classifications were based on the Toxicological and Ecological Data of the substances/mixtures in the Section 11 and 12.

4 First-aid measures

Description of First Aid Measures**General Information**

Ensure medical personnel are aware of exposure and take precautions for their personal protection; see Section 8 for the information of personal protection.

After Inhalation

Remove victim from exposure to fresh air. Keep person at rest. Provide oxygen if person is not breathing. Supply fresh air and to be sure call for a doctor. In case of unconsciousness place patient stably in side position for transportation. Supply fresh air; consult doctor in case of complaints.

After Skin Contact

Remove all contaminated clothing and wash before reuse. Wash contaminated skin with water and soap and rinse thoroughly. Seek immediate medical advice.

After Eye Contact

Immediately bathe eyes for 15 minutes under running water. Immediately remove contact lenses if present. Continue rinsing. Seek immediate medical advice.

After Swallowing

If victim is unconscious; never give anything by mouth. If victim is conscious; rinse out mouth and give victim small amounts of water. Seek medical treatment in case of complaints.

After Exposure Seek medical treatment in case of complaints.

Information for Doctor Have chemical containers, labels and/or (M)SDS ready when calling or visiting a medical center.

Indication of any Immediate Medical Attention and Special Treatment Needed

After frequent or high intense exposure, the following medical tests are recommended:

eye tests

skin tests

Check section 11 Toxicological Information for further relevant information.

Additional Information

For additional information, please consult the corresponding first aid measures in the most current version of Emergency Response Guidebook which is produced by the US Department of Transportation.

5 Fire-fighting measures

Extinguishing Media**Suitable Extinguishing Agent(s)**

Use fire fighting measures and extinguishing agents that suit the environment.

In case of fire, suitable extinguishing agents are:

Alcohol resistant foam.

Dry chemical or fire-extinguishing powder.

Carbon dioxide (CO₂).

Water spray or water fog.

Unsuitable Extinguishing Agent(s) Water with full jet

Firefighting Procedures

Isolate fire and deny unnecessary entry.

Immediately withdraw all personnel from the area in case of rising sound from venting safety device.

Eliminate all ignition sources if safe to do so.

Do not extinguish fire unless flow can be stopped.

Fight fire remotely due to the risk of explosion.

(Contd. on page 4)

US

Safety Data Sheet acc. to OSHA HCS

Print Date 05/12/2015

Revision Date 05/12/2015

Trade Name: EP1056LV BLACK A

(Contd. of page 3)

Burning liquids may be moved by flushing with water; protect personnel and minimize property damage.
Contain fire water runoff if possible to prevent environmental pollution.
No information available.
Fight fire from protected location or safe distance.
Contain fire water runoff if possible to prevent environmental pollution.

· **Special Hazards Arising in Fire**

Will not burn unless preheated.
In case of fire, following can be released:
Nitrogen oxides
Toxic vapors
Carbon dioxide (CO₂) and Carbon monoxide (CO)
Calcium oxide (CaO)

· **Advice for Firefighters**

If employees are expected to fight fires, they must be trained and equipped as stated in the OSHA fire brigades standard (29 CFR 1910.156).
As with any fire, wear positive-pressure self-contained breathing apparatus and full protective gear that are NIOSH approved.

· **Additional Information** Be Caution! Finely dispersed substance may form explosive mixtures in air.

6 Accidental release measures

· **Personal Precautions**

Avoid contact with skin, eyes, and clothing.
Do not breathe gas, vapors, dusts or mists if their inhalable particles occur during use.
Ensure personnel take precautions for their personal protection during clean up; see Section 8 for the specific requirements.

· **Environmental Precautions**

Keep away from sewage system or other water courses; do not penetrate ground/soil.
Inform respective authorities in case of any seepage to the environment.

· **Cleaning Up Methods**

Ensure adequate ventilation.
Eliminate all ignition sources.
Keep unauthorized personnel away.
For large spills:
Shut off source of leak if safe to do so.
Dike and contain.
Remove with vacuum trucks or pump to storage/salvage vessels.
Allow molten product to cool.
Absorb residues with liquid-binding materials.
Avoid confined spaces, such as sewers, because of the possibility of an explosion.
For small spills:
Ventilate and wash area after clean-up is complete.
Collect spills in suitable and properly labeled containers.
Do not use solvents unless following safe handling practices and within the recommended exposure guidelines.
Dispose contaminated chemicals as waste according to Section 13.

· **Additional Information** No further relevant information.

7 Handling and storage

· **Handling**

· **Precautions for Safe Handling**

Obtain special instruction before use; do not handle until all safety precautions have been read and understood.
Do not breathe gas, vapors, dusts or mists if their inhalable particles occur during handling.
Wear respiratory protection when handling.
Keep away from incompatible material(s).
Avoid any release into the environment.
Observe all the personal protection requirements in Section 8.

(Contd. on page 5)

Safety Data Sheet
acc. to OSHA HCS

Print Date 05/12/2015

Revision Date 05/12/2015

Trade Name: EP1056LV BLACK A

(Contd. of page 4)

Information about Protection Against Explosions and Fires

Will not burn unless preheated.
Keep away from heat, sparks, open flame and other ignition sources during handling.
Dust can combine with air to form an explosive mixture.

Storage

Requirements to be Met by Storerooms and Receptacles

Store in a well-ventilated place; provide ventilation for receptacles.
Keep stored in accordance with local, regional, national, and international regulations.

Information about Storage in One Common Storage Facility

Store away from incompatible material(s).
Store away from foodstuffs.
Avoid release to the environment.

Additional Information No further relevant information.

8 Exposure controls/personal protection

Engineering Measures or Controls

Exposure Limit Values that Require Monitoring at the Workplace

1317-65-3 Calcium Carbonate

TEEL	Short-term value: 15.0 mg/m ³ Long-term value: 60.0 mg/m ³ SCAPA, 2008
------	--

67762-90-7 Siloxanes and Silicones, di-Me, reaction products with silica

OSHA PEL	Short-term value: 15 mg/m ³
US ACGIH	Short-term value: 10 mg/m ³

1333-86-4 Carbon black

PEL	Long-term value: 3.5 mg/m ³
REL	Long-term value: 3.5* mg/m ³ *0.1 in presence of PAHs; See Pocket Guide Apps.A+C
TLV	Long-term value: 3* mg/m ³ *inhalable fraction

14808-60-7 Quartz

PEL	see Quartz listing
REL	Long-term value: 0.05* mg/m ³ *respirable dust; See Pocket Guide App. A
TLV	Long-term value: 0.025* mg/m ³ *as respirable fraction

Other Engineering Measures or Controls

Ventilation rates should be matched to conditions.
If applicable, use process enclosure(s), local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits.

Personal Protective

General Protective and Hygienic Measures

Avoid any contact with eye.
Do not eat, drink or smoke during work.
Keep food, drink or feed away from working area.
Contaminated work clothing is not allowed out of workplace.
Clean hands and exposed skin thoroughly after work and before breaks.

Personal Protective Equipment (PPE)

Breathing Equipment

Caution! Improper use of respirators is dangerous.
In case of brief exposure or low pollution, use a respiratory filter device.
In case of intensive or longer exposure, use a positive-pressure respiratory protective device that is independent of circulating air.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Print Date 05/12/2015

Revision Date 05/12/2015

Trade Name: EP1056LV BLACK A

(Contd. of page 5)

Hand Protection



Protective gloves

Selection of glove material should take into consideration the penetration times, rates of diffusion, and the degradation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Suggested glove type(s):

Nitrile Gloves
Butyl Rubber Gloves

Eye Protection



Tightly sealed goggles

Body Protection No relevant information.

Additional Information

All protective clothing (suits, gloves, footwear, headgear) should be clean, available every day, and put on before work. The Engineering measures or controls, and PPE recommendations are only guidelines and may not apply to every situation. For additional information, please consult the corresponding requirements under OSHA 29 CFR 1910.94-95, and 29 CFR 1910.132-138.

9 Physical and chemical properties

Information on Basic Physical and Chemical Properties

Appearance:

· Form:	Liquid
· Color:	Black
· Odor:	Mild epoxy odor
· Odor Threshold:	Not determined.

· **PH-Value:** Not determined.

Change in Condition:

· Melting Point:	Not determined.
· Boiling Point:	>200 °C (>392 °F)
· Flash Point:	>200 °C (>392 °F)
· Decomposition Temperature:	Not determined.
· Auto-ignition Temperature:	Not determined.
· Flammability:	Not determined.
· Explosion:	Not determined.
· Explosion Limits:	
· Lower:	Not determined.
· Upper:	Not determined.

· Vapor Pressure:	Not determined.
· Vapor Density:	not determined
· Density at 25 °C (77 °F):	1.23 g/cm ³ (10.264 lbs/gal)

Solubility in or Miscibility with

· Water:	Not miscible or difficult to mix.
· Segregation coefficient LogPow (n-octanol/ water):	Not determined.
· Henry's Law Constant:	Not determined.

(Contd. on page 7)

US

Safety Data Sheet
acc. to OSHA HCS

Print Date 05/12/2015

Revision Date 05/12/2015

Trade Name: EP1056LV BLACK A

(Contd. of page 6)

· Viscosity:

· **Dynamic at 20 °C (68 °F):**

23000 mPas

· **Kinematic:**

Not determined.

· Additional Information

No further relevant information.

10 Stability and reactivity

· **Physical Hazard(s)** Not a regulated reactive or physical hazard under GHS.

· **Hazardous Reactivity and Chemical Stability**

exothermic reactions including polymerization may occur in contact with amines, strong acids, strong bases, alcohols, strong oxidizing agents and excessive heat.

Stable under normal conditions of use, storage and temperatures.

· **Thermal Decomposition and Conditions to be Avoided**

Keep away from incompatible material(s).

Thermally decomposes during fire or high heat; keep away from heat, sparks, open flame and other ignition sources.

· **Possibility of Other Hazardous Reaction(s)**

May ignite on contact with fluorine.

No further relevant information available.

· **Incompatible Material(s)**

Oxidizing agents

Acids

Bases (Alkalis)

Alum, Fluorine, Ammonium salts, Mercury/hydrogen mixture, and Magnesium

· **Hazardous Decomposition Product(s)**

Irritating fumes

Thermally decomposes during fire or very high heat. See Section 5 for fire hazards evolved during thermal decomposition.

· **Hazardous Polymerization Product(s)** An exothermic reaction may occur with amines.

· **Additional Information** No further relevant information.

11 Toxicological information

· **Acute Toxicity**

· Oral

25068-38-6 Bisphenol-A-(epichlorohydrin) epoxy resin

Oral	LD50	11400 mg/kg (rat) 15600 mg/kg (mouse) Reference: NLM Toxnet (2010).
------	------	---

74398-71-3 1, 2, 3-Propanetriyl ester of 12-(oxiranylmethoxy)-9-octadecanoic acid

Oral	LD50	> 5000 mg/kg (rat) Reference: Hexion (M)SDS (2003).
------	------	--

1317-65-3 Calcium Carbonate

Oral	LD50	6450 mg/kg (rat) Reference: Imerys (M)SDS (2008).
------	------	--

· **Potential Health Effect(s):** Not a classified acute oral hazard.

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Print Date 05/12/2015

Revision Date 05/12/2015

Trade Name: EP1056LV BLACK A

(Contd. of page 7)

Dermal

25068-38-6 Bisphenol-A-(epichlorohydrin) epoxy resin

Dermal	LD50	20000 mg/kg (rabbit) (Test guideline not available) > 1270 mg/kg (mouse) > 2000 mg/kg (rat) > 1600 mg/kg (rabbit); however, there was no fixed test result available; classification was not possible without further information. Reference: Royce (M)SDS (2011) and ChemID (2010).
--------	------	--

74398-71-3 1, 2, 3-Propanetriyl ester of 12-(oxiranylmethoxy)-9-octadecanoic acid

Dermal	LD50	> 2000 mg/kg (rabbit) Reference: Hexion (M)SDS (2003).
--------	------	---

1317-65-3 Calcium Carbonate

Dermal	LD50	(-) No data available.
--------	------	---------------------------

Potential Health Effect(s): Not a classified acute dermal hazard.

Inhalative

25068-38-6 Bisphenol-A-(epichlorohydrin) epoxy resin

Inhalative	LC50/4 h	(Test species: n/a) (Toxicity not expected based on the acute oral data)
------------	----------	--

74398-71-3 1, 2, 3-Propanetriyl ester of 12-(oxiranylmethoxy)-9-octadecanoic acid

Inhalative	LC50/4 h	(No data available)
------------	----------	---------------------

1317-65-3 Calcium Carbonate

Inhalative	LC50/4 h	(-) No data available.
------------	----------	---------------------------

Potential Health Effect(s): No further relevant information; classification is not possible.

Skin Corrosion or Irritation

25068-38-6 Bisphenol-A-(epichlorohydrin) epoxy resin

Corrosion/Irritation	irritating (rabbit) Acute skin irritation was mild, through repeated and prolonged exposure may cause severe irritation. The substance was classified as Category 2 by GHS-J. Reference: HSNO CCID (2010) and GHS-J (2006).
----------------------	--

74398-71-3 1, 2, 3-Propanetriyl ester of 12-(oxiranylmethoxy)-9-octadecanoic acid

Corrosion/Irritation	slightly irri. (Test species: n/a) Based on manufacturer's test result, the substance was slightly irritating to skin (Category 3). Reference: Hexion (M)SDS (2003).
----------------------	--

1317-65-3 Calcium Carbonate

Corrosion/Irritation	moderately (-) The substance is moderately irritating based on the PH = 9.5 with concentration of 50g/L of water at 20C. moderately (rabbit) (Draize test) 500 mg/24h, the pure substance shows no irritating effect, however, the impurities or degradation products may lead to irritant effects on the sweating skin due to alkalinity. Reference: IUCLID dataset of CAS No. 471-34-1 (2000).
----------------------	--

Potential Health Effect(s):

Causes skin irritation.
In contact with skin, may cause:
redness and pain

Eye Serious Damage or Irritation

25068-38-6 Bisphenol-A-(epichlorohydrin) epoxy resin

Damage/Irritation	irritating (rabbit) The substance caused eye irritation (Category 2A) based on the dermal effect to rabbit skin.
-------------------	---

74398-71-3 1, 2, 3-Propanetriyl ester of 12-(oxiranylmethoxy)-9-octadecanoic acid

Damage/Irritation	(No data available)
-------------------	---------------------

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Print Date 05/12/2015

Revision Date 05/12/2015

Trade Name: EP1056LV BLACK A

(Contd. of page 8)

1317-65-3 Calcium Carbonate

Damage/Irritation	slightly (Human) The substance is slightly irritating to the eyes. Reference: IUCLID Dataset of CAS No. 471-34-1 (2000).
	not irritating (rabbit) No toxic effect when applied to surface of rabbit eyes Reference: ACToR of CAS No. 471-34-1 (2010).

Potential Health Effect(s):

Causes serious eye irritation.
In contact with eye, may cause:
redness and pain

Respiratory or Skin Sensitization
25068-38-6 Bisphenol-A-(epichlorohydrin) epoxy resin

Sensitization	Skin	sensitizing (Human) Based on positive results from skin sensitization tests on human volunteers and guinea pigs, GHS-J classified the substance as a dermal sensitizer. Reference: GHS-J (2006).
	Respiratory	(No data available)

74398-71-3 1, 2, 3-Propanetriyl ester of 12-(oxiranylmethoxy)-9-octadecanoic acid

Sensitization	Skin	sensitizing (Test species: n/a) Based on manufacturer's test result, the substance was a skin sensitizer, and the sensitization can be severe in susceptible individuals. Reference: Hexion (M)SDS (2003).
	Respiratory	(No data available)

1317-65-3 Calcium Carbonate

Sensitization	Skin	(-) No data available.
	Respiratory	(-) No data available.

Potential Health Effect(s):

May cause an allergic skin reaction.
No relevant information for respiratory sensitization; classification is not possible.

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

Germ Cell Mutagenicity
25068-38-6 Bisphenol-A-(epichlorohydrin) epoxy resin

Mutagenicity	positive (Chinese hamster lung fibroblast cells) (In Vitro (Chromosomal Aberration)) In Vitro (Chromosomal Aberration; Chinese hamster lung fibroblast cells) - Positive without metabolic activation; negative with metabolic activation. Positive (salmonella typhimurium) (In Vitro (Ames assay)). Due to the absence from In Vivo tests, it was not possible to make a conclusion of mutagenicity of the substance. Reference: NLM CCRIS (2010).
--------------	---

74398-71-3 1, 2, 3-Propanetriyl ester of 12-(oxiranylmethoxy)-9-octadecanoic acid

Mutagenicity	(No data available)
--------------	---------------------

1317-65-3 Calcium Carbonate

Mutagenicity	negative (-) The pure substance is not listed as a carcinogen by NTP, IARC or OSHA. Reference: Imerys (M)SDS (2008).
--------------	--

Potential Health Effect(s): No further relevant information; classification is not possible.

(Contd. on page 10)

US

Safety Data Sheet
acc. to OSHA HCS

Print Date 05/12/2015

Revision Date 05/12/2015

Trade Name: EP1056LV BLACK A

(Contd. of page 9)

Carcinogenicity

25068-38-6 Bisphenol-A-(epichlorohydrin) epoxy resin

Carcinogenicity *negative (Test species: n/a) (Not listed by ACGIH, IARC, NTP, or OSHA) (Mouse)*
1 out of 4 cases with female mice showed positive carcinogenic results after a repeated dermal application with 10% concentration of the substance for two years. When considering all of the evidence, the substance was not classified as a carcinogen.
Reference: Dow (M)SDS (2010).

74398-71-3 1, 2, 3-Propanetriyl ester of 12-(oxiranylmethoxy)-9-octadecanoic acid

Carcinogenicity *negative (Test species: n/a) (not listed as a Carcinogen by NTP, IARC or OSHA)*

1317-65-3 Calcium Carbonate

Carcinogenicity *negative (salmonella typhimurium) (Preincubation)*
In Vitro - Negative with and without metabolic activation.
Reference: NLM TOXNET of CAS No. 471-34-1 (2010).

Potential Health Effect(s): Not a known Carcinogen.

Reproductive Toxicity

25068-38-6 Bisphenol-A-(epichlorohydrin) epoxy resin

Reproductive Toxi. *negative (Test species: n/a) (no reproductive or developmental effect observed)*
There was no reproductive or developmental effect observed at dosing levels that were toxic to parental animals.
Reference: GHS-J (2006).

74398-71-3 1, 2, 3-Propanetriyl ester of 12-(oxiranylmethoxy)-9-octadecanoic acid

Reproductive Toxi. *(No data available)*

1317-65-3 Calcium Carbonate

Reproductive Toxi. *(rat)*
Up to 1.25% diet of the substance for 6 weeks prior to mating and during gestation and found no adverse effects.
Reference: ACToR of CAS No. 471-34-1 (2010).

Potential Health Effect(s): Not a known Reproductive hazard.

Specific Target Organ Toxicity - Single Exposure

25068-38-6 Bisphenol-A-(epichlorohydrin) epoxy resin

STOT-Single *Target: None (Rats and Mice) (No effect after single oral doses)*
Somnolence (general depressed activity) and dyspnea were observed after a single oral application with 11400 mg/kg to rats, or 15600 mg/kg to mice of the substance. However, the dose levels were both outside of the guidance value ranges.
Reference: NLM Toxnet (2010).

74398-71-3 1, 2, 3-Propanetriyl ester of 12-(oxiranylmethoxy)-9-octadecanoic acid

STOT-Single *(No data available)*

1317-65-3 Calcium Carbonate

STOT-Single *(Human)*
Inhalation 0.005 mg/L for 3 hours:
target organs - systemic toxicity
May affect nasal function and cause nasal symptoms.

Ingested up to 15g of the substance:
target organs - systemic toxicity
Symptoms included: fatigue, anorexia, nausea and vomiting, an elevated blood pressure, hemoconcentration, leukocytosis, metabolic alkalosis, elevated body weight and hypokalemia.
Reference: ACToR of CAS No. 471-34-1 (2010).

(rat)
Exposed to 0.0812 mg/L for 90 minutes/ after 21 hr. No effect on lung weight, macrophage concentration, or histopathology.
Reference: ACToR of CAS No. 471-34-1 (2010).

Potential Health Effect(s): Not a known hazard to organs upon single exposure.

(Contd. on page 11)

Safety Data Sheet

acc. to OSHA HCS

Print Date 05/12/2015

Revision Date 05/12/2015

Trade Name: EP1056LV BLACK A

(Contd. of page 10)

Specific Target Organ Toxicity - Repeated Exposure

25068-38-6 Bisphenol-A-(epichlorohydrin) epoxy resin

STOT-Repeated Target: N/A (guinea pig) (insufficient data for classification)
 With dermal application of the substance for 55 days, increased seromucoid concentrations, decreased lactate-dehydrogenase (LDH), and decreased leucyl-naphthylamidase (LNA) were observed in the test animals. Meanwhile, the substance caused a toxic effect on blood components of female guinea-pigs with greater effects on pregnant animals. However, there was no detail available regarding the dose level or test guideline, classification was thus not possible.
 Reference: HSN0 CCID (2010).

74398-71-3 1, 2, 3-Propanetriyl ester of 12-(oxiranylmethoxy)-9-octadecanoic acid

STOT-Repeated (No data available)

1317-65-3 Calcium Carbonate

STOT-Repeated (Human)
 Target organs - Systemic toxicity
 Symptoms: Infrequent instances of hypercalcemia with alkalosis, calcinosis, azotemia, renal dysfunction, GI hemorrhage and vomiting or aspiration through nasogastric tube seem to predispose to the disorder.
 Reference: ACToR of CAS No. 471-34-1.

Potential Health Effect(s): No further relevant information; classification is not possible.

Aspiration Hazard

25068-38-6 Bisphenol-A-(epichlorohydrin) epoxy resin

Aspiration Hazard (No data available)

74398-71-3 1, 2, 3-Propanetriyl ester of 12-(oxiranylmethoxy)-9-octadecanoic acid

Aspiration Hazard (No data available)

1317-65-3 Calcium Carbonate

Aspiration Hazard (-)
 No data available.

Potential Health Effect(s): No relevant information; classification is not possible.

Additional Information No further relevant information.

12 Ecological information

Aquatic Environmental Toxicity

25068-38-6 Bisphenol-A-(epichlorohydrin) epoxy resin

Algae Toxicity (No data available)
 Crustacean Toxicity 1.4 - 1.7 mg/l (Daphnia magna (water flea)) (EC50 (48 hrs))
 Fish Toxicity 1.41 mg/l (Oryzias latipes (Rice fish)) (LC50 (96 hrs))
 3.1 mg/l (Pimephales promelas (fathead minnow)) (LC50 (96 hrs))
 Based on the non-rapid degradability and the acute LC50 < 10 mg/L, the substance is classified as a Chronic-2 environmental hazard.
 Reference: Dow (M)SDS (2010) and CHRIP (2010).

74398-71-3 1, 2, 3-Propanetriyl ester of 12-(oxiranylmethoxy)-9-octadecanoic acid

Algae Toxicity (No data available)

Crustacean Toxicity (No data available)

Fish Toxicity (No data available)

1317-65-3 Calcium Carbonate

Algae Toxicity (static) 56000 mg/l (Gambusia affinis (western mosquitofish)) (LC50 (24 - 96 hrs))
 Reference: ACToR of CAS No. 471-34-1 (2010).

(Contd. on page 12)

US

Safety Data Sheet

acc. to OSHA HCS

Print Date 05/12/2015

Revision Date 05/12/2015

Trade Name: EP1056LV BLACK A

(Contd. of page 11)

Crustacean Toxicity	(<i>Poecilia Latipinna</i> (Saifin molly)) Exposure period: 96 hrs. NOEC > 200 mg/L Reference: IUCLID Dataset of CAS No. 471-34-1 (2000).
Fish Toxicity	(-) The substance is not toxic to aquatic organisms. Reference: Canada DSL of CAS No. 471-34-1 (2007).
Micro-organism toxic	(-) The substance is not toxic to aquatic organisms. Reference: Canada DSL of CAS No. 471-34-1 (2007).

Aquatic Environmental Toxicity Assessment: Toxic to aquatic life with long lasting effects.

Degradability and Stability

25068-38-6 Bisphenol-A-(epichlorohydrin) epoxy resin

Biodegradation	non-biodegrad. (Test species: n/a) (Biodegradation (OECD TG 302B; 28 days) = 12%) (Activated Sludge) (OECD TG 301C; 4 weeks; Conc. 100 mg/L) Biodegradation (Indirect Analysis from BOD) = 0% Biodegradation (Direct Analysis from HPLC) = 0% The substance is non-biodegradable. Reference: Dow (M)SDS (2010) and CHRIP (2010).
Persistence	(Test species: n/a) (This substance is persistent) Reference: Canada DSL (2007) and CHRIP (2010).
Photodegradation	6.69E-11 cm ³ /molecule-sec (OH radical) (Half-life (T _{1/2}) = 1.92 hrs) However, photolysis in water is negligible. Reference: Dow (M)SDS (2010).
Stability in water	(No data available)

74398-71-3 1, 2, 3-Propanetriyl ester of 12-(oxiranylmethoxy)-9-octadecanoic acid

Biodegradation	non-biodegrad. (Test species: n/a) (Non-biodegradable due to persistent property) Based on the persistent assessment according to Canada DSL, the substance is expected to be non-degradable in the environment.
Persistence	(Test species: n/a) (The substance is persistent) Reference: Canada DSL (2007).
Photodegradation	(No data available)
Stability in water	(No data available)

1317-65-3 Calcium Carbonate

Biodegradation	(-) The test is not applicable since this substance is inorganic and not soluble in water. Reference: IUCLID Dataset of CAS No. 471-34-1 (2000).
Photodegradation	positive cm ³ /molecule-sec (-) The substance is persistent. Reference: ACToR of CAS No. 471-34-1 (2010).
Stability in water	(-) No data available.

Bioaccumulation and Distribution

25068-38-6 Bisphenol-A-(epichlorohydrin) epoxy resin

(Contd. on page 13)

US

Safety Data Sheet

acc. to OSHA HCS

Print Date 05/12/2015

Revision Date 05/12/2015

Trade Name: EP1056LV BLACK A

(Contd. of page 12)

BCF	0.56-42 (Cyprinus carpio) (The substance is low-bioaccumulative) BCF (28 days; Concentration: 10 µg/L) = 0.56 - 0.67, 3.3 - 4.2 BCF (28 days; Concentration: 1 µg/L) = 5.6 - 6.8, 33 - 42 Reference: CHRIP (2010).
Koc	1800 - 4400 L/kg (soil) Potential for mobility in soil is moderate. Reference: Dow (M)SDS (2010).
LogPow	3.7 - 3.9 (Test species: n/a) Reference: Dow (M)SDS (2010).
74398-71-3 1, 2, 3-Propanetriyl ester of 12-(oxiranylmethoxy)-9-octadecanoic acid	
BCF	(Test species: n/a) (The substance is not bioaccumulative) Reference: Canada DSL (2007).
Koc	(No data available)
LogPow	(No data available)
1317-65-3 Calcium Carbonate	
BCF	(-) No data available.
Environment fate	(-) No data available.
Koc	(-) No data available.
LogPow	(-) No data available.

· **Degradability and Bioaccumulation Assessment:** Non-rapidly degradable, and low bioaccumulative.

· **Additional Information** No further relevant information.

13 Disposal considerations

· **Hazardous Waste List**

· **Description:** It may be necessary to contain and dispose of the substance/mixture as a hazardous waste.

· **Waste Treatment Recommendation:**

Generation of waste should be avoided or minimized wherever possible.

Chemical waste, even small quantities, is neither allowed to be poured down drains, sewage system or waterways; nor disposed with household garbage.

Dispose of contents/containers in accordance with local, regional, national, and international regulations.

· **Unused and Uncontaminated Packagings**

· **Recommendation** Dispose of according to your local waste regulations.

14 Transport information

· **UN-Number**

· **DOT, ADR, IMDG, IATA**

UN3082

· **UN Proper Shipping Name**

Environmentally hazardous substance, liquid, N.O.S. (Bisphenol-A-(epichlorohydrin)epoxy resin)

(Contd. on page 14)

US

Safety Data Sheet

acc. to OSHA HCS

Print Date 05/12/2015

Revision Date 05/12/2015

Trade Name: EP1056LV BLACK A

(Contd. of page 13)

Transport hazard class(es)
DOT, IMDG, IATA

Class
Label

 9 Miscellaneous dangerous substances and articles
 9

ADR

Class
Label

 9 (M6) Miscellaneous dangerous substances and articles
 9

Packing group
DOT, ADR, IMDG, IATA

III

Environmental Hazards:

Product contains environmentally hazardous substances: Bisphenol-A-(epichlorohydrin) epoxy resin

Marine Pollutant:

 Yes
 Symbol (fish and tree)

Special Marking (ADR):

Symbol (fish and tree)

Special Marking (IATA):

Symbol (fish and tree)

Special Precautions:

Warning: Miscellaneous dangerous substances and articles

Danger Code (Kemler):

90

EMS Number:

F-A,S-F

Transport in Bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

Transport/Additional Information:
DOT
Remarks:

Special marking with the symbol (fish and tree).

ADR
Excepted quantities (EQ)

 Code: E1
 Maximum net quantity per inner packaging: 30 ml
 Maximum net quantity per outer packaging: 1000 ml

IMDG
Limited quantities (LQ)

5L

Excepted quantities (EQ)

 Code: E1
 Maximum net quantity per inner packaging: 30 ml
 Maximum net quantity per outer packaging: 1000 ml

UN "Model Regulation":

UN3082, Environmentally hazardous substances, liquid, n.o.s. (Bisphenol-A-(epichlorohydrin) epoxy resin), 9, III

(Contd. on page 15)

Safety Data Sheet

acc. to OSHA HCS

Print Date 05/12/2015

Revision Date 05/12/2015

Trade Name: EP1056LV BLACK A

(Contd. of page 14)

15 Regulatory information

USA Regulation Lists

SARA (Superfund Amendments and Reauthorization Act of 1986)

Section 302 (Extremely Hazardous Substances)

None of the ingredients is listed.

Section 313 (Toxics Release Inventory (TRI) reporting)

None of the ingredients is listed.

Section 311/312 (Hazardous Chemical Inventory Reporting)

25068-38-6	Bisphenol-A-(epichlorohydrin) epoxy resin	A, C	60-70%
74398-71-3	1, 2, 3-Propanetriyl ester of 12-(oxiranylmethoxy)-9-octadecanoic acid	A, C	10-20%
1317-65-3	Calcium Carbonate	A, C	10-20%
1333-86-4	Carbon black	A, C	0.1-<1%

Hazard Abbreviations for SARA 311/312

A - Acute Health Hazard
 C - Chronic Health Hazard
 F - Fire Hazard
 R - Reactive Hazard
 S - Sudden Release of Pressure Hazard

TSCA (Toxic Substances Control Act)

25068-38-6	Bisphenol-A-(epichlorohydrin) epoxy resin
74398-71-3	1, 2, 3-Propanetriyl ester of 12-(oxiranylmethoxy)-9-octadecanoic acid
1317-65-3	Calcium Carbonate
67762-90-7	Siloxanes and Silicones, di-Me, reaction products with silica
1333-86-4	Carbon black
14808-60-7	Quartz

Proposition 65

Chemicals Known to Cause Cancer

This product may also contain extremely small amounts of one or more naturally occurring materials known to the State of California to cause cancer, birth defects or other reproductive harm.

1333-86-4	Carbon black
14808-60-7	Quartz

Chemicals Known to Cause Reproductive Toxicity for Females

None of the ingredients is listed.

Chemicals Known to Cause Reproductive Toxicity for Males

None of the ingredients is listed.

Chemicals Known to Cause Developmental Toxicity

None of the ingredients is listed.

Carcinogenic Categories

EPA (Environmental Protection Agency)

None of the ingredients is listed.

IARC (International Agency for Research on Cancer)

14808-60-7	Quartz	1
------------	--------	---

NTP (National Toxicology Program)

14808-60-7	Quartz	K
------------	--------	---

TLV (Threshold Limit Value Established by ACGIH)

1333-86-4	Carbon black	A4
14808-60-7	Quartz	A2

(Contd. on page 16)

Safety Data Sheet

acc. to OSHA HCS

Print Date 05/12/2015

Revision Date 05/12/2015

Trade Name: EP1056LV BLACK A

(Contd. of page 15)

NIOSH-Ca (National Institute for Occupational Safety and Health)

14808-60-7 Quartz

International Regulation Lists
Canadian Domestic Substance Listings:

25068-38-6	Bisphenol-A-(epichlorohydrin) epoxy resin
74398-71-3	1, 2, 3-Propanetriyl ester of 12-(oxiranylmethoxy)-9-octadecanoic acid
1317-65-3	Calcium Carbonate
67762-90-7	Siloxanes and Silicones, di-Me, reaction products with silica
1333-86-4	Carbon black
14808-60-7	Quartz

Canadian Ingredient Disclosure list (limit 0.1%)

None of the ingredients is listed.

Canadian Ingredient Disclosure list (limit 1%)

None of the ingredients is listed.

Chinese Chemical Inventory of Existing Chemical Substances:

25068-38-6	Bisphenol-A-(epichlorohydrin) epoxy resin
74398-71-3	1, 2, 3-Propanetriyl ester of 12-(oxiranylmethoxy)-9-octadecanoic acid
1317-65-3	Calcium Carbonate
67762-90-7	Siloxanes and Silicones, di-Me, reaction products with silica
1333-86-4	Carbon black
14808-60-7	Quartz

Japanese Existing and New Chemical Substance List:

25068-38-6	Bisphenol-A-(epichlorohydrin) epoxy resin
1317-65-3	Calcium Carbonate
67762-90-7	Siloxanes and Silicones, di-Me, reaction products with silica
1333-86-4	Carbon black
14808-60-7	Quartz

Korean Existing Chemical Inventory:

25068-38-6	Bisphenol-A-(epichlorohydrin) epoxy resin
74398-71-3	1, 2, 3-Propanetriyl ester of 12-(oxiranylmethoxy)-9-octadecanoic acid
1317-65-3	Calcium Carbonate
67762-90-7	Siloxanes and Silicones, di-Me, reaction products with silica
1333-86-4	Carbon black
14808-60-7	Quartz

European Pre-registered substances:

25068-38-6	Bisphenol-A-(epichlorohydrin) epoxy resin
74398-71-3	1, 2, 3-Propanetriyl ester of 12-(oxiranylmethoxy)-9-octadecanoic acid
1317-65-3	Calcium Carbonate
67762-90-7	Siloxanes and Silicones, di-Me, reaction products with silica
1333-86-4	Carbon black
14808-60-7	Quartz

REACH - Substances of Very High Concern (SVHC) List:

None of the ingredients is listed.

Restriction of Hazardous Substances Directive (RoHS) list:

None of the ingredients is listed.

US

(Contd. on page 17)

Safety Data Sheet acc. to OSHA HCS

Print Date 05/12/2015

Revision Date 05/12/2015

Trade Name: EP1056LV BLACK A

(Contd. of page 16)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department Issuing (M)SDS:** Product Safety Department
- **Contact:** msds@resinlab.com

Abbreviations and acronyms:

ACGIH: American Conference of Governmental Industrial Hygienists
ACToR: US EPA Aggregated Computational Toxicology Resource
ADR: European Agreement Concerning the International Carriage of Dangerous Goods by Road
CAS: Chemical Abstracts Service (division of the American Chemical Society)
CCR: Canadian Categorization Results
CCRIS: US NLM TOXNET Chemical Carcinogenesis Research Information System
CHRIP: Japan NITE Information on Biodegradation and Bioconcentration of the Existing Chemical Substances in the Chemical Risk Information Platform
ChV: Chronic Value
DOT: US Department of Transportation
DSL: Canada Domestic Substance List
ECHA: European Chemicals Agency's Dissemination portal with information on chemical substances registered under REACH
HMIS: US National Paint & Coatings Association (NPCA) Hazardous Materials Identification System
HPVIS: US EPA High Production Volume Information System
HSDB: US NLM TOXNET Hazardous Substances Databank
HSNO CCID: New Zealand Hazardous Substances and New Organisms Chemical Classification Information Database
IARC: International Agency for Research on Cancer developed by United Nations World Health Organisation (WHO)
IATA-DGR: Dangerous Goods Regulations (DGR) by the International Air Transport Association (IATA)
ICAO-TI: Technical Instructions (TI) by the International Civil Aviation Organization (ICAO)
ICSC: International Chemical Safety Cards
IMDG: International Maritime Dangerous Goods; the principal international rules for International Carriage of Dangerous Goods by SEA under the Recommendations on the Transport of Dangerous Goods by United Nations (RTDG)
IUCLID: EU REACH International Uniform Chemical Information Database
LC50/LD50: Lethal Concentration/Dose, 50 percent
N/a: Not available or Not applicable
NFPA: US National Fire Protection Association
NIOSH: US National Institute of Occupational Safety and Health
NITE: National Institute of Technology and Evaluation, Japan
NLM TOXNET: US National Library of Medicine Toxicology Data Network
OECD: Organisation for Economic Co-operation and Development
OSHA: US Occupational Safety and Health Administration
P: Marine Pollutant
RCRA: Resource Conservation and Recovery Act (USA)
REACH: EU Registry, Evaluation and Authorisation of Chemicals
RID: the Regulations Concerning the International Carriage of Dangerous Goods by Rail; published by the Central Office for International Carriage by Rail (OTIF)
RTDG: the Recommendations on the Transport of Dangerous Goods by United Nations (UN)
RTECS: US Registry of Toxic Effects of Chemical Substances
SARA: US Superfund Amendments and Reauthorization Act
SIDS: OECD existing chemicals Screening Information Data Sets
TEEL: Temporary Emergency Exposure Limit developed by US Subcommittee on Consequence Assessment and Protective Actions (SCAPA) of US Department of Energy (DOE)
TOXLINE: US NLM bibliographic database search system
TSCA: US Toxic Substance Control Act
BCF: Bioconcentration Factor
ESIS: European Chemical Substances Information System
Koc: Partition coefficient, soil Organic Carbon to water
SVHC: EU ECHA Substance of Very High Concern

· **Date of preparation / last revision** 05/12/2015 / 2